

# DIFFERENTIAL PRESSURE GAUGES AND MANOMETERS MM Series

Liquid column manometer for HVAC applications

The MM series liquid column manometers are engineered for HVAC/R applications. The MM series devices detect air and non-corrosive gas pressures (differential, vacuum and positive) and provide a clear analog display of the measured values.

The MM series is designed with a reservoir to protect the manometer liquid from leaking into the duct during overpressure situation.

#### MM series device features include:

- field adjustable zero point calibration
- pressure limit stickers

#### The MM series device options offer:

• level bubble



# **SIMILAR PRODUCTS**

- DPG series differential pressure gauges
- MMU series U-tube manometers

# **APPLICATIONS**

MM series devices are commonly used in HVAC/R systems for:

- fan, blower and filter monitoring
- pressure and flow monitoring
- pressure monitoring in cleanrooms

# **MODEL SUMMARY**

| Description             | Model     | Product code | Measurement range (Pa) |
|-------------------------|-----------|--------------|------------------------|
| Liquid column manometer | MM±50     | 107.001.001  | -500+50                |
| Liquid column manometer | MM100     | 107.002.001  | -200100                |
| Liquid column manometer | MM±100500 | 107.003.001  | -1000100               |
| Liquid column manometer | MM200600  | 107.004.001  | 0200600                |

Copyright HK Instruments 2016 www.hkinstruments.fi Datasheet Version 3.0 2016

# **DIFFERENTIAL PRESSURE GAUGES AND MANOMETERS MM Series**

Liquid column manometer for HVAC applications

# **SPECIFICATIONS**

#### **Performance**

# Accuracy:

MM±50

±1 Pa

MM100

±1 Pa

MM±100500

-100...0 Pa ±5 Pa

0...500 Pa ±25 Pa MM200600

0...200 Pa ±5 Pa

200...600 Pa ±25 Pa

#### Overpressure:

Max pressure 200 kPa

#### **Technical specifications**

#### Media compatibility:

Dry air or non-aggressive gases

# Measuring units:

#### Measuring ranges:

-50...0...50 Pa

-20...0...100 Pa

-100...0...100 Pa 0...200...600 Pa

# **Environment:**

Operating temperature:

-40...+60 °C

## Gauge fluid:

Red: s.g. 0.786 kg/dm (15  $^{\circ}$ C)

(Isopar M)

MM±50 RED MM100 RED

MM±100500 RED

MM200600 RED

## **Physical**

Case:

ABS

Cover: **PMMA** 

Knobs:

Polycarbonate (PC)

O-ring:

Nitrile rubber (NBR)

Weight:

420 g

#### **Safety**

Product equipped with integral reservoir to prevent gauge fluid leakage during overpressure situation.



